



PLASTRONIC®

Dimensions Data

Item	Text area dimension	Overall dimensions	Label recommended
LAM-048x010-YL	48x10mm	70x14mm	40x6mm / 38.1x6.4mm - 6mm tape
LAM-055x015-YL	55x15mm	100x15mm	50x10mm / 50.8x9.5mm - 9mm tape
LAM-085x015-YL	85x15mm	130x15mm	75x10mm / 76.2x9.5mm - 9mm tape

Physical data Top-Film:

Polyester (0-PET)
Thickness: 50µ
Halogen free
Colour: Transparent

Adhesive:

Long life adhesive especially selected for lamination application.
UV resistant pressure sensitive acrylic adhesive.
High adhesion on low energy surfaces.
Acrylic based adhesive

Liner:

One side siliconized, totally chlorine-free (TCF), wood-free Kraft paper.
Weight: 120 g/m².
Color: White

Carrier-Film:

UV stabilized Polypropylene (PP)
Thickness: 500 µ
Colour: Yellow
Halogen free

Standard colours:
Yellow

Operating temperature:
-10°C to +60°C.

Application temperature:
>+10°C.

Service Lifetime:
DTI has tested the product according to DS 1094.4: Expected service lifetime for the product is minimum 10 to 15 years without delamination.

General remark:

Long-term heat- and/or UV exposure may result in discoloration of the product.



Notes:

This information and data is believed to be accurate and reliable. Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of this date, Link Solutions makes no representations as to the completeness or accuracy thereof. We place at your disposal the technical information necessary for the correct use of our products. As conditions and methods of use are beyond our control, that the person receiving the same will make their own determination as to the suitability for their purpose.

We reserve the right to modify characteristics with the aim of improving the product and adapting it to the requirements of the market.