

Adhesive lined, heat shrinkable, wraparound sleeve

Watertight Insulation
 Cable Range 12mm to 150mm
 Thermal Indicator
 Quick and easy to install
 Can be cut to length

RPR wraparound sleeve incorporates a stainless steel channel which is simply slid into position and keeps the wraparound tubing in place during installation, but if desired can be easily removed when the adhesive is set

Technical Data

General

Installation temperature >150°C
 Longitudinal change +0% -10%

Electrical

Dielectric strength 20 kV/mm minimum

Thermal

Heat ageing 168hrs at 150°C
 4 hours at 200°C

Low temperature flexibility 4 hours at -40°C

Flammability

Non flame retardant

Chemical

Fluid resistance Fuels
 Hydraulic fluids
 Oils 23°C to ISO1817

Specifications

RoHS Compliant

Size (mm)	Application Range (mm)	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Layflat dim Supplied (mm)	Layflat dim Recovered (mm)	Wall Supplied (mm)	Wall Recovered (mm)
34/10	12–21	34	10	110	32	0.3	2.4
53/13	15–32	53	13	170	41	0.4	2.3
84/20	23–50	84	20	270	63	0.4	2.3
107/29	34–65	107	29	340	92	0.4	2.3
143/36	42–86	143	36	455	114	0.4	2.3
250/98	111–150	250	98	785	308	0.4	1.7

Standard colour: Black

Full details on technical specifications, test methods and values are available on request.